

[IPN Home](#) | [Search](#) | [Order](#) | [Shopping Cart](#) | [Login](#) | [Site Map](#) | [Help](#)



JP3188146A2: RESIN COMPOSITION AND LAMINATE

[View Images \(1 pages\)](#) | [View INPADOC only](#)

Country: **JP Japan**

Kind:

Inventor(s): **TOKOO MAKIO
SATO TOSHIAKI
HIROFUJI SATOSHI
AOYAMA AKEMASA
MARUYAMA HITOSHI**

Applicant(s): **KURARAY CO LTD**
[News, Profiles, Stocks and More about this company](#)

Issued/Filed Dates: **Aug. 16, 1991 / Dec. 15, 1989**

Application Number: **JP1989000326837**

IPC Class: **C08L 23/26; B32B 27/28; C08K 5/54; C08L 29/02; C08L 77/00;**

Abstract: **Purpose:** To obtain a resin composition excellent in processability and gas barrier properties and capable of retort sterilization by compounding a specified ethylene/vinyl acetate copolymer saponificate and a specified aromatic polyamide each in a specified amount.

Constitution: This composition is prepared from 40-95wt.% ethylene/vinyl acetate copolymer saponificate of an ethylene content of 20-60mol% and a degree of saponification of the vinyl acetate component of at least 95mol% and 60-5wt.% aromatic polyamide essentially consisting of an aromatic dicarboxylic acid (e.g. isophthalic acid) and xylylenediamine and containing a 3-10C aliphatic dicarboxylic acid component (e.g. adipic acid) and/or a 3-10C aliphatic diamine component (e.g. hexamethylenediamine).
COPYRIGHT: (C)1991,JPO&Japio

Other Abstract Info: **CHEMABS 115(26)281661W CAN115(26)281661W DERABS C91-284796
DERC91-284796**

Foreign References: **(No patents reference this one)**



Alternative
Searches



[Patent Number](#)



[Boolean Text](#)




[Advanced Text](#)

[Nominate this
invention
for the Gallery...](#)

[Browse](#)


[U.S. Class
by title](#)


[U.S. Class
by number](#)

TDB
[IBM Technical
Disclosure Bulletin](#)

[Privacy](#) | [Legal](#) | [Gallery](#) | [IP Pages](#) | [Advertising](#) | [FAQ](#) | [Contact Us](#)